

Specification (M-K2)

Main Amp:

1. Circuit Type	Push Pull, Ultra Linear Class AB1, Mono Block Stereo
2. Nom. Power	100 + 100 Watts
3. Frequency Response	14 Hz ~ 50 KHz
4. Distortion	Less than 0.2% @ 70 Watts
5. Input Sensitivity	0.1 V for Full Output
6. Input Impedance	100 K Ohm
7. Output Impedance	4 & 8 Ohm
8. Tube Complement	KT-88 (EH) x 4, 12AU7 (EH) x 4, 12AX7LPS x 2
9. Inputs	Tape, CD, Aux-1, Aux-2
10. Tape Out	For Tape Recording
11. Power Amp Function	Connectable to Pre Amp & AV-Amp (Pre Out)
12. Output Protector	Protection and Noise Cancel for Speaker Output by Selection of Power Amp

Power Supply:

1. Circuit Type	Mono Block 1 PCB Type
2. Power Transformer	600 VA
3. AC Power (50 / 60 Hz)	100, 120, 220, 230, 240 Volt Selectable for World Wide
4. Bias Voltage Regulator	Built-In-Regulator for Bias Voltage
5 Electrolytic Capacitor	1800 UF / 450V x 4
6. AC Fuse	10 Amp / 250 V x 1
7. DC Fuse (B-Plus)	3 Amp / 250 V x 2 for Vcc
8. AC Cord	3 Conductor w / Ground
9. Power Supply Cable	Male Coupling for Power Supply, Female for Main Amp
10. Finish	Aluminum Chassis Anodized
11. Weight	15 Kg
12. Dimension	177 (W) x 455 (D) x 185 (H)