

Specification (M-Vitali V5)

Main Amp:

1. Circuit Type	Push Pull, Ultra Linear Class AB1, Mono Block Stereo
2. Nom. Power Output	80 + 80 Watts (RMS)
3. Frequency Response	16 Hz – 50 KHz
4. Distortion	Less than 0.2% at 70 Watts
5. Input sensitivity	0.5V for full Output
6. Input Impedance	100 K Ohm
7. Output Impedance	4 & 8 Ohm
8. Tube Complement	SV6550C * 4, ECC82 (12AU7) * 4, ECC83 (12AX7) * 2
9. Inputs (Unbalanced)	Tape, CD, Aux-1, Aux-2
10. Tape Out	For Recording
11. Power Amp Function	Connectable to Pre Amp & AV- Amp
12. Remote Control	On / Off – S/W

Power Supply:

1. Circuit Type	Mono Block in 2 PCB
2. Power Transformer	600 VA (50 / 60 Hz)
3. AC Power Selectable	EU-Type: 220V, 230V, 240V / US-Type: 100V, 110V, 120V
4. Electric Capacitor	680 UF / 400V * 6
5. Power Consumption	160 Watts
6. AC Fuse	10 Amp / 250V * 1
7. DC Fuse	4 Amp / 250V * 2
8. AC – Cord	3 Conductor with Ground

Chassis:

1. Finish	Stainless, Aluminum & Wood Chassis
2. Weight	28 Kg
3. Dimension	210 (H) * 450 (W) * 500 (D)

SIS-Form: 080107 (Vitali-V5)

All data are subject to change without prior notice.